



# DRIVER SPECIFICATION—UC22

INTEGRATED DRIVER FOR UNICAB FIXTURE

## MODEL LIST

Model Name	Rated Input Voltage	Rated Output Power	Rated Output Voltage	Output Current	Class
ULD12W-36-C0300	120–277 VAC	12W	30–42 VDC	290–310mA	2

## SPECIFICATIONS

Parameters	Symbols	Test Conditions/Comment	Min	Typ	Max	Units				
<b>INPUT</b>										
Input Voltage	V <sub>IN</sub>	0-10V Dimming	100		305	VAC				
Input Frequency	f <sub>line</sub>		47	50/60	63	Hz				
Input Current	I <sub>IN</sub>	Full Load, V <sub>IN</sub> = 120 VAC			0.10	A				
		Full Load, V <sub>IN</sub> = 230 VAC			0.06	A				
		Full Load, V <sub>IN</sub> = 277 VAC			0.05	A				
<b>GENERAL CHARACTERISTICS</b>										
Power Factor	PF	100% Load, V <sub>IN</sub> = 120 VAC	0.95							
		100% Load, V <sub>IN</sub> = 230 VAC	0.85							
		100% Load, V <sub>IN</sub> = 277 VAC	0.80							
Efficiency	η	Full Load, V <sub>IN</sub> = 120 VAC	87	88	89	%				
		Full Load, V <sub>IN</sub> = 230 VAC	84	85	86	%				
		Full Load, V <sub>IN</sub> = 277 VAC	82	83	84	%				
Turn On Delay Time	T <sub>on</sub> _delay	Cold Start, No Dimmer		0.3	0.5	S				
Leakage Current	I <sub>leakage</sub>	V <sub>IN</sub> = 277 VAC/60Hz			0.5	mA				
<b>OUTPUT</b>										
Output Voltage	V <sub>OUT</sub>		30	36	40	V				
Output Current	I <sub>OUT</sub>	0-10V Dimming	15		320	mA				
Output Current	I <sub>OUT</sub>	No Dimming	280	300	320	mA				
<b>0-10V</b>										
The 0-10V is a dimming manner that can be used to dim the output voltage via a standard commercial wall dimmer (0-10VDC) or an external control voltage source (0-10VDC) or external resistor. The dimming range is 100% V <sub>OUT</sub> to 5% V <sub>OUT</sub> . When V <sub>DIM</sub> is 8-10VDC, the output voltage maintains 100% V <sub>OUT</sub> , and when V <sub>DIM</sub> is below 0.6V, the output voltage is 5% V <sub>OUT</sub> .										
Absolute Maximum Voltage on 0-10V Pin	V <sub>DIM</sub>		-2		15	V				
Source Current on 0-10V Dimming Pin	I <sub>DIM</sub>			100		uA				
<b>PROTECTION</b>										
Over Voltage Protection	V <sub>OVP</sub>	Latch Off Mode			45	V				
Short Circuit Protection		Power supply will recover automatically after fault conditions are removed.								
No Load Protection		Power supply will recover automatically after loading.								
<b>ENVIRONMENT</b>										
Storage Temperature	T <sub>Storage</sub>	Humidity: 5% RH to 95% RH	-40	-	85	°C				
Operating Relative Humidity	H <sub>a</sub>	Non Condensing	10		90	%				
<b>OTHERS</b>										
Life Time	T <sub>Life</sub>	Full Load, 120 VAC Input, 50 °C Case Temp.	50			KHrs				
Dimension L × W × H			6.69" × 1.22" × 0.83" (170 mm × 31 mm × 21 mm)							
<b>SAFETY COMPLIANCE</b>										
ETL Listed		UL8750 Compliance to UL1310 Class 2, CSA-C22.2 No. 107.1								
<b>EMC COMPLIANCE</b>										
FCC Part 15B		Conducted Emission Test and Radiated Emission Test								
Note: Unless otherwise specified, all the above parameters are measured at ambient temperature of 25 °C and V <sub>IN</sub> = 100–277 VAC.										