



DIRECT VIEW 400 (INDOOR)

DK-SERIES | LINEAR LED LIGHTING


Fixture Type: _____

Project: _____

Location: _____



Cut Intervals: 25mm (0.98")



Depth: 1.2mm

MODEL:	DK24K-24V	DK27K-24V	DK3K-24V	DK35K-24V	DK41K-24V	DK5K-24V
Kelvin	2400K	2700K	3000K	3500K	4100K	5000K
Lumens	340 lm/ft	357 lm/ft	390 lm/ft	410 lm/ft	440 lm/ft	473 lm/ft

PRODUCT FEATURES

- Suitable for most direct view applications
- 90+ CRI
- Dimmable
- 50,000 hour life
- 5-year warranty
- UL-listed for indoor
- 3M™ industrial adhesive backing
- For use with 24V power supplies

SPECIFICATIONS

Series	DK - Direct View 400 (Indoor)
Input Voltage	24V DC / Constant Voltage
Watts per Foot	3.3W/ft @ Maximum Run Length
Beam Spread	120°
Max Run Length	Unlimited, power every 18ft
Cut Intervals	0.98" (25mm)
Dimensions	1/2" (12mm) x 1/16" (1.2mm)
CRI	90+
Diode	Epistar 2016
Dimming Options	PWM, Triac, 0-10V, DMX, Hi-lume
Temp Range	-40°F (-40°C) to 149°F (65°C)

KELVIN COLOR TEMPERATURE SCALE



TOTAL WATTAGE USED AT EACH LENGTH

1ft	2ft	3ft	4ft	5ft	6ft	7ft	8ft	9ft	10ft	11ft	12ft	13ft	14ft	15ft	16ft	17ft	18ft
4.3	8.7	12.9	17.5	21.4	25.3	29.1	32.6	36.5	40	43.2	46.1	48.9	51.5	53.4	55.8	58	59.4

Conforms to ANSI/UL Standard 2108
 Certified to CAN/CSA Standard C22.2 No. 250.0

