



# DIRECT VIEW 700 (OUTDOOR)

DV-SERIES | RUBBER COATED | LINEAR LED LIGHTING


Fixture Type: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_



Cut Intervals: 25mm (0.98")



Width: 13.2mm  
(14.2mm end cap)

Depth: 6mm  
(9 mm endcap)

MODEL:	DV27K-WR-24V	DV3K-WR-24V	DV35K-WR-24V	DV41K-WR-24V	DV5K-WR-24V
<b>Kelvin</b>	2700K	3000K	3500K	4100K	5000K
<b>Lumens</b>	658 lm/ft	670 lm/ft	690 lm/ft	704 lm/ft	723 lm/ft
<b>Rating</b>	IP67	IP67	IP67	IP67	IP67

## PRODUCT FEATURES

- Suitable for most direct view applications
- 90+ CRI
- Dimmable
- 50,000 hour life
- 5-year warranty
- UL-listed for indoor and outdoor use
- 3M™ Industrial adhesive backing
- For use with 24V power supplies

## SPECIFICATIONS

Series	DV - Direct View 700 (Outdoor)
Input Voltage	24V DC / Constant Voltage
Watts per Foot	5.3W/ft @ Maximum Run Length
Beam Spread	120°
Max Run Length	Unlimited, power every 15ft
Cut Intervals	.098" (25mm)
End Cap Dimensions	9/16" (14.2mm) x 3/8" (9mm)
Tape Dimensions	17/32" (13.2mm) x 1/4" (6mm)
CRI	90+
Diode	Epistar 2016
Dimming Options	PWM, Triac, 0-10V, DMX, Hi-lume
Temp Range	-40°F (-40°C) to 149°F (65°C)

## KELVIN COLOR TEMPERATURE SCALE



## TOTAL WATTAGE USED AT EACH LENGTH

1ft	2ft	3ft	4ft	5ft	6ft	7ft	8ft	9ft	10ft	11ft	12ft	13ft	14ft	15ft
7.7	15.1	22.3	29.5	35.8	41.9	47.2	52.4	57.8	62.7	66.1	70	73.3	76.7	80.1

Conforms to ANSI/UL Standard 2108  
Certified to CAN/CSA Standard C22.2 No. 250.0

