



SOLID COLOR (INDOOR/OUTDOOR)


RED-GREEN-BLUE-AMBER | RUBBER COATED

LINEAR LED LIGHTING

Fixture Type: _____

Project: _____

Location: _____



MODEL:	PHRK-WR-24V	PHGK-WR-24V	PHBK-WR-24V	PHAK-WR-24V
Color	RED (620-625nm)	GREEN (525-527.5nm)	BLUE (465-467.5nm)	AMBER (600-605nm)
Lumens	109 lm/ft	197 lm/ft	60 lm/ft	107 lm/ft
Rating	IP67	IP67	IP67	IP67

PRODUCT FEATURES

- Dimmable
- 50,000 Hour Life
- 5-year Warranty
- UL-listed for Indoor and Outdoor Use
- 3M™ Industrial Adhesive Backing
- For Use with 24V Power Supplies

SPECIFICATIONS

Series	Solid Color (Indoor/Outdoor)
Input Voltage	24V DC / Constant Voltage
Watts per Foot	3.2W/ft @ Maximum Run Length
Beam Spread	120°
Max Run Length	Unlimited, power every 30ft
Production Intervals	3.938" (100mm)
End Cap Dimensions	0.5" (12.2mm) × 0.375" (9mm)
Tape Dimensions	0.4375" (11.2mm) × 0.25" (6mm)
Diode	Epistar 2835
Dimming Options	PWM, Triac, 0-10V, DMX, Hi-lume
Temp Range	-40°F (-40°C) to 149°F (65°C)

SOLID LED COLOR SELECTION



TOTAL WATTAGE USED AT EACH LENGTH

1ft	2ft	3ft	4ft	5ft	6ft	7ft	8ft	9ft	10ft	11ft	12ft	13ft	14ft	15ft
4.2	8.5	12.7	16.8	21	25.4	29.2	32.9	36.9	40.5	44.2	48	51.4	54.6	57.7
16ft	17ft	18ft	19ft	20ft	21ft	22ft	23ft	24ft	25ft	26ft	27ft	28ft	29ft	30ft
60.7	64.3	67	70.4	71.8	75.2	77.7	80	83	85.1	86.6	88.7	91.2	93.7	94.6

Conforms to ANSI/UL Standard 2108
 Certified to CAN/CSA Standard C22.2 No. 250.0

