

XERO™ (INDOOR/OUTDOOR)

LINE VOLTAGE | LINEAR LED LIGHTING | 3000K

Fixture Type:	
Project:	
Location:	

	0	0			0	0
LED Interva	ls: 5/8"					,
						Width: 15mm (18mm end cap)
						Depth: 8mm

PRODUCT FEATURES

- ETL-Listed for indoor and outdoor use
- 120V Input
- 172 lumens per foot
- Dimmable
- 50,000 hour life
- IP65 Rating

KELVIN COLOR TEMPERATURE SCALE



REQUIRED COMPONENT*

X-FML-PLUG (58-inch plug-in power feed)



^{*} Power feed required. Please purchase a plug-in power feed when placing order.

SPECIFICATIONS

Model	X3K-WH (Indoor./Outdoor)
Input Voltage	120V AC
Watts/ft	2.5
Beam Spread	120°
Max Run Length	140ft
Cut Intervals	18" (45.72cm)
End Cap Dimensions	11/16" (18mm) x 7/16" (11mm)
Tape Dimensions	9/16" (15mm) x 5/16" (8mm)
CRI	80
Diode	Epistar 5050
Dimming Options	Triac
Temp Range	-40°F (-40°C) to 149°F (65°C)

OPTIONAL ACCESSORIES

X-CH-AL-1M (1-meter aluminum mounting channel)

X-CLIP (Economic plastic mounting clip)













