



# MARGOT 218

LINEAR EASY-SPEC™



### KELVIN COLOR TEMPERATURE SCALE



Fixture Type: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### FEATURES

- Optional seamless lensing up to 100ft
- 100 to 1000 lumens per foot
- Field replaceable light source
- 50,000 hour lamp life
- Dimmable to 1%
- Anodized finish

### SPECIFICATIONS

Input Voltage	24V DC / Constant Voltage
CRI	90+
Diode	Epistar
Dimming Options	PWM, Triac, 0-10V
Temp Range	-40°F to 149°F
Channel Height	37.5mm (1-1/2")
Channel Width	35mm (1-3/8")

### PART NUMBER BUILDER

Example:

**218-I-36-DV-35K-WH-CP-SV-ULV**

Model	Setting	Length (Unlimited) <sup>1</sup>	Output	CCT	Lens	Mounting	Finish	Power Supply
218	I						SV	ULV
218	I - Indoor	Inches	<b>PJ</b> - 100+lm/ft <b>PL</b> - 200+lm/ft <b>PH</b> - 300+lm/ft <b>DK</b> - 400+lm/ft <b>PQ</b> - 500+lm/ft <b>DV</b> - 700+lm/ft <b>VT</b> - 1000+lm/ft  <b>HC3RGBW</b> - Color Changing ( <i>Only available in 3K</i> )	<b>24K</b> - 2400 Kelvin <b>27K</b> - 2700 Kelvin <b>3K</b> - 3000 Kelvin <b>35K</b> - 3500 Kelvin <b>41K</b> - 4100 Kelvin <b>5K</b> - 5000 Kelvin	<b>NA</b> - None <b>WH</b> - White <b>SWH</b> - Seamless White ( <i>SWH for direct view applications only</i> )	<b>CP</b> - Mounting Clips <b>SP</b> - Suspension <b>WL</b> - Wall Clip	<b>SV</b> - Silver ( <i>Custom Finishes Available</i> )	<b>ULV</b> - Universal Power Supply <sup>2</sup>

<sup>1</sup>Light Source is installed in field allowing for seamless lensing and unlimited run lengths

<sup>2</sup>120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

For use with us Light Source

Certified to CAN/CSA Standard C22.2 No. 250.0

