





# MELISSA 006


LINEAR EASY-SPEC™



White Lens (WH) Mounting Clips (PC)



### KELVIN COLOR TEMPERATURE SCALE



Fixture Type: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### FEATURES

- Optional seamless lensing up to 100ft
- 100 to 1000 lumens per foot
- Field replaceable light source
- 50,000 hour lamp life
- Dimmable to 1%
- Anodized finish

### SPECIFICATIONS

Input Voltage	24V DC / Constant Voltage
CRI	90+
Diode	Epistar
Dimming Options	PWM, Triac, 0-10V
Temp Range	-40°F to 149°F
Channel Height	16mm (5/8")
Channel Width	16mm (5/8")

### PART NUMBER BUILDER

Example:

**006-I-36-PL-35K-WH-CP-SV-ULV**

Model	Setting	Length (Unlimited) <sup>1</sup>	Output	CCT	Lens	Mounting	Finish	Power Supply
<b>006</b>	<b>I</b>					<b>CP</b>	<b>SV</b>	<b>ULV</b>
<b>006</b>	<b>I</b> - Indoor	<b>Inches</b>	<b>PJ</b> - 100+lm/ft <b>PL</b> - 200+lm/ft <b>PH</b> - 300+lm/ft <b>PQ</b> - 500+lm/ft  <b>NRGBW</b> - Color Changing <i>(Only available in 3K)</i>	<b>24K</b> - 2400 Kelvin <b>27K</b> - 2700 Kelvin <b>3K</b> - 3000 Kelvin <b>35K</b> - 3500 Kelvin <b>41K</b> - 4100 Kelvin <b>5K</b> - 5000 Kelvin	<b>NA</b> - None <b>WH</b> - White	<b>CP</b> - Mounting Clips	<b>SV</b> - Silver <i>(Custom Finishes Available)</i>	<b>ULV</b> - Universal Power Supply <sup>2</sup>

<sup>1</sup>Light Source is installed in field allowing for seamless lensing and unlimited run lengths

<sup>2</sup>120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

For use with c us Light Source

Certified to CAN/CSA Standard C22.2 No. 250.0

